

Product Description – Water based organic pigment dispersion

PIGMARAMA® BLACK KBL

Application Water based organic pigment dispersion for emulsion paints, woodstains, latex, paper etc. Tinting acrylate latices.

Specifications	Pigment class:	Carbon Black
	C.I. No:	Bl.7
	Cas No:	1333-86-4
	Physical Appearance:	Viscous paste
	Pigment content(%):	Apr. %35
	Specific gravity(g/cm ³):	Apr. 1,19
	pH:	9,0±1 (direct at 20°C)
	Viscosity:	Max.300 cps (Brook.RV, 20°C, S#5, 50 rpm)
	Packing:	30 kg PE drums
	Storage:	Store in tightly closed original packaging in a dry and cool place between 5 °C and 35 °C. It can withstand temperatures as low as 0°C, but it is water-based so it is recommended to protect it from frost. Product is stable for 2 years under the appropriate conditions.
	Safety:	No special precautions.

Fastness properties

	Light fastness ⁽¹⁾	Weathering ⁽²⁾	Resistance to Acid	Resistance to Alkali
5%	8	5	5	5
1%	8	5	5	5

(1) ISO 105 B02

(2) ISO 105 B04

The information in this data sheet is given as a service only and is not to be taken as a guarantee.

KY72 / TBD 34 086 Rev. No: 02 Date: 25.05.2024 Page: 1/1

KEMİTEKS Kimya San. ve Tic. A.Ş.
Omerli Mah. Gulce Sokak No:13 34555
Hadimkoy / Arnavutkoy / ISTANBUL
Tel: +90-212-771 28 28 Faks : +90-212-771 28 37
info@kemiteks.com
www.kemiteks.com