

Product Description – Water based organic pigment dispersion

## PIGMARAMA<sup>®</sup> BLACK CB

Application Water based organic pigment dispersion for emulsion paints, woodstains, latex, paper etc. Tinting acrylate latices.

|                |                                       |  |
|----------------|---------------------------------------|--|
| Specifications | Pigment class:                        | Carbon Black   |
|                | C.I. No:                              | Bl.7   |
|                | Cas No:                               | 1333-86-4  |
|                | Physical Appearance:                  | Viscous paste  |
|                | Pigment content(%):                   | Apr. %40   |
|                | Specific gravity(g/cm <sup>3</sup> ): | Apr. 1,19  |
|                | pH:                                   | 9,0±1 (direct at 20°C)   |
|                | Viscosity:                            | Max.2000 cps<br>(Brook.RV, 20 <sup>0</sup> C, S#5, 50 rpm )  |
|                | Packing:                              | 30 kg PE drums / 1000Kg bulk   |
|                | Storage:                              | Store in tightly closed original packaging in a dry and cool place between 5 °C and 35 °C. It can withstand temperatures as low as 0°C, but it is water-based so it is recommended to protect it from frost. Product is stable for 2 years under the appropriate conditions. |
|                | Safety:                               | No special precautions.  |

Fastness properties

|    | Light fastness <sup>(1)</sup> | Weathering <sup>(2)</sup> | Resistance to Acid | Resistance to Alkali |
|----|-------------------------------|---------------------------|--------------------|----------------------|
| 5% | 8                             | 5                         | 5                  | 5                    |
| 1% | 8                             | 5                         | 5                  | 5                    |

(1) ISO 105 B02

(2) ISO 105 B04

The information in this data sheet is given as a service only and is not to be taken as a guarantee.

KY72 / TBD 34 086 Rev. No: 03 Date: 25.05.2024 Page: 1/1

**KEMİTEKS Kimya San. ve Tic. A.Ş.**  
Omerli Mah. Gulce Sokak No:13 34555  
Hadimkoy / Arnavutkoy / ISTANBUL  
Tel: +90-212-771 28 28 Faks : +90-212-771 28 37  
[info@kemiteks.com](mailto:info@kemiteks.com)  
[www.kemiteks.com](http://www.kemiteks.com)